

Professional SDI Monitor – HDVS Series

- CH-L270-2HDVSB-SDI



Feature

- Multi-Function Display
- True 10 bits Color processing engine
- Independent color management(ICM)
- Dynamic contrast control(DCC)
- Supported 1080p Full HD
- Build-in 2W+2W speaker
- VESA standard bracket
- Wall mountable capability

Monitor Connection



Specifications

| Model | CH-L270-2HDVSB-SDI |
|------------------------|-------------------------------------------------------------------------------------------------|
| LCD panel | 27" |
| Visible area (mm) | 597.6x 336.15 |
| Picture format | 16:9 |
| Max. resolution | 1920x1080 |
| Pixel dot pitch (mm) | 0.31125 x0.31125 |
| Colours | 16.7M |
| Brightness | 300 cd/m ² [LED] |
| Contrast | 5000:1 |
| Response time(Tr/Tf) | 7/5 ms |
| View angle (U/D/L/R) | 89/89/89/89 |
| Video input /output | 1x /1x SDI (BNC) |
| Full HD input | 1x Full HD (A Type) |
| Audio input (R/L) | 2x (RCA) |
| PC input | 1x VGA input (D-Sub 15 pin) 1x DVI-D input |
| Earphone out | 1xPhone jack ,3.5ψ |
| Speaker | 2x built-in speaker (2 watt) |
| SDI standards | 3G-SDI[SMPTE 424M] HD-SDI[SMPTM 292M] SD-SDI[SMPTE 259M] |
| SDI Video support | [3G] 1080P50/60(4:2:2) [HD]720P@50/60Hz,1080i@50/60Hz,1080p25/30Hz [SD]NTSC/60Hz,PAL/50Hz |
| SDI Video bandwidth | 2.97Gpbs&2.975/1.001Gpbs |
| SDI Cable Transmission | 3G-SDI[100Meter],HD-SDI[200Meter],SD-SDI[300Meter] _(5C2V orRG6Cable) |
| OSD setting | Yes |
| Power input | AC 100-240V 50/60Hz, Adapter DC 12V/5A |
| Power consumption | Approx. 35watt |
| Dimensions (WxHxD) mm | 658 x 396.6 x 60.5 |
| Weight | 7.2kg |
| Protective front glass | Option |
| Operating temperature | 0° to 50° C |

Subject to technical changes without prior notice. Error excepted.