

## SC-17P



A cost-effective 17" surveillance display with the quality, connectivity and performance essential for any security environment.

With the AG Neovo SC-17P, security centres can keep an eye on budgets without losing sight of performance. Digital and analogue video inputs, including looping BNC I/O, minimise installation cost. Auto NTSC/PAL detection, settings key lock and auto settings adjustment reduce maintenance hassle. Quick signal-switching and rapid response time improve surveillance efficiency, while built-in speakers provide an additional level of security. All this and more make the SC-17P the perfect value display choice for any security environment.

- > High 1280 × 1024 SXGA resolution
- > Anti-Burn-in™ technology
- > Built-in Image Enhancer: 3D Comb Filter/Deinterlace/Noise Reduction
- > Versatile connectivity (BNC in/out, S-Video, VGA, HDMI, Audio in/out)
- > Looping BNC video inputs for multiple connections
- > Quick signal-switching time ( ≤ 0.8 sec. )
- > NTSC/PAL auto-detection
- > Selectable signal source
- > PC compatible
- > Built-in speakers
- > Key lock function
- > Auto-adjustment for optimal setting
- > Security socket
- > VESA standard wall mount
- > Tilt capacity from -2° ~ 20°
- > Rigorous screening of the components for mission-critical 24/7 applications
- > Kensington® Security socket



# SC-17P

| Specifications        |                             | SC-17P  |
|-----------------------|-----------------------------|---|
| Panel                 | Panel Type                  | LED-Backlit TFT LCD   |
|                       | Panel Size                  | 17.0" (432 mm)  |
|                       | Max. Resolution             | SXGA 1280 x 1024  |
|                       | Pixel Pitch                 | 0.264 mm  |
|                       | Brightness                  | 250 cd/m <sup>2</sup>   |
|                       | Contrast Ratio              | 1000:1  |
|                       | Viewing Angle (H/V)         | 170°/160°   |
|                       | Display Colour              | 16.7M   |
|                       | Response Time               | 3 ms  |
| Horizontal Resolution | TV Lines                    | 600TVL (NTSC), 600TVL (PAL)   |
|                       | Frequency (H/V)             | H: 31.5 kHz - 80 kHz<br>V: 50 Hz - 75 Hz                                |
| Input                 | Analogue                    | 15-Pin D-Sub  |
|                       | HDMI                        | HDMI  |
|                       | CVBS                        | BNC x 1   |
|                       | S-Video                     | 4-Pin mini DIN  |
| Out                   | CVBS                        | BNC x 1   |
| Audio                 | Audio In                    | 3.5ø mm audio jack  |
|                       | Audio Out                   | 3.5ø mm audio jack  |
|                       | Speaker                     | 1W x 2  |
| Power                 | Power Supply                | Internal  |
|                       | Power Requirements          | 100 ~ 240V, 50 - 60Hz   |
|                       | Consumption                 | < 18 W (On)<br>< 0.5 W (Off)  |
| Plug & Play           | VESA                        | EDID  |
| Operating Conditions  | Temperature                 | 0 °C ~ 40 °C  |
|                       | Humidity                    | 10% ~ 85%   |
| Storage Conditions    | Temperature                 | -20 °C ~ 60 °C  |
|                       | Humidity                    | 10% ~ 95%   |
| Mounting              | VESA FPMPI                  | Yes (100 x 100mm)   |
| Tilt                  | Tilt                        | -2° ~ 20°   |
| Dimensions            | Product (W x H x D)         | 372 x 385.2 x 184mm<br>(14.6" x 15.2" x 7.2")                           |
|                       | Packaging (W x H x D)       | 450 x 467 x 138mm<br>(17.7" x 18.4" x 5.4")                             |
|                       | Weight                      | Product Weight<br>Packaged Weight                                       |
| Regulation Approval   | Certifications & Compliance | CB, FCC, CE, REACH, GOST-R, WEEE, RoHS                                  |
| Accessories           | Supplied                    | User manual, power cord, 15-Pin D-Sub cable, audio cable, warranty card |



Stylish and slim design ideal for professional security environments



Built-in speakers enable more rigorous security monitoring



Looping BNC video inputs allow multiple display connections



Video versatility, including VGA, HDMI, S-Video and BNC In/Out

