

Caméra à Transmission 3G / 4G



H.265 3G/4G HD IP Camera
SIM-Cam30E/F
SIM-Cam50A

- ◆ Caméra IP avec routeur LTE intégré
- ◆ Résolution 2592 x 1944 (ajustable)
- ◆ Triple stream H.265 / H.264 / MJPEG
- ◆ Routeur 3G / 4G intégré
- ◆ Boîtier Outdoor étanche
- ◆ Projecteur IR automatique 40/45m
- ◆ Enregistreur Full HD sur carte SD
- ◆ Détecteur de mouvement programmable avec envoi d'alertes.
- ◆ Consultation à distance par Internet, PC, iPhones, SmartPhones



• Features:

- Embedded RTOS design, Dual Core DSP
- High-performance compression tech
- Dual stream to adjust to the network flexibly
- Optional function: POE, Audio input& output, Alarm-in, Micro SD Card, Wi-Fi.
- Motion detection alarm/ DWDR
- HD video, Compression: H.265/MJPEG/H.264
- Low LUX: 1.0LUX (Color) /0.1LUX (B&W)
- BLC; 3D-DNR; DEFOG; DWDR
- Compatible with Hikvision Private [Protocol](#)
- Support P2P, iPhone, iPad, Android
- Smart ROI(4 ROI region)
- Support 3G/4G network

4G: TDD-LTE: 2570-2620 / 1880-1920 / 2300-2400
FDD-LTE / TDD-LTE / CDMA(CDMA2000 / 1x
EVDO Rev.A 3G: 800/1900MHz)

3G: TD-SCDMA: 2010-2025 / 1880-1920 MHz
WCDMA : 850/900/1900/2100MHz
CDMA2000 : 800/1900MHz

Trappe étanche sous la caméra
Emplacements (slots) pour
Carte SIM (transmission)
Carte mémoire SD (enregistrement)
Accès aux réglages de l'objectif
(zoom et focus)



Model	SIM-Cam30E	SIM-Cam30F	SIM-Cam50A
Sensor/DSP	1/3" OV 4689 + 3516D	1/3" OV4689 +3516A	1/3" OV 5658 + 3516A
Day/Night	ICR		
Min.Illumination	Low LUX: 1.0LUX (Color) 0.1LUX (B&W)	Low LUX: 0.6LUX (Color) 0.08LUX (B&W)	Low LUX: 0.05LUX (Color) 0.01LUX (B&W)
Lens	2.8-12mm, Megapixel HD Manual Zoom Lens		
IR LED	Array IR*2pcs		
IR Distance	40-45M		
White Balance	Manual/Automatic		
OSD	YES		
Electronic Shutter	1/2000 ~ 1/1000		
VIDEO			
Compression	H.265/H.264/MJPEG		
Max Image Resolution	2048*1536	2048*1520(3.0MP)	2592*1944(5.0MP)
Frame Rate	25/30FPS		
Bit Rate	32Kpbs~16Mpbs(Adjustable),CBR/VBR		
WDR	>80dB dWDR	>80dB dWDR	>80dB dWDR
AUDIO(Optional)			
NETWORK			
Protocol	TCP/IP, HTTP, DHCP, DNS, DDNS, UDP,RTP, RTP/RTCP,RTSP, PPPoE, SMTP, NTP, UPnP, FTP,etc		
4G standard	TDD-LTE/FDD-LTE,WCDMA		
Compliance	ONVIF 2.4		
PC Client & Browser	mCMS, IE,danale		
Mobile Phone	iPhone,iPad,Android		
INTERFACE			
Video Output	RJ45		
LAN	1 RJ45 10/100 ethernet port		
UIM SIM card slot	1pcs		
4G antenna	1pcs		
Micro SD Card slot	1pcs		
GENERAL			
Working Temperature	-10 C ~ + 50 C		
Working Humidity	0% ~ 90%		
Power Supply	DC12V/9.6W max. / PoE 802.3af		
Dimension	306(W)x96(H)x87(D)mm		
Weight	1600 gr		