



4-en-1

## CAMERA MINIATURE ANALOGIQUE IP-M2710SW

- 4 Vidéos coaxiales sans latence
- Résolution FHD 1920 x 1080
- Ultra Sensible
- Objectif Mégapixel 4 ou 16 mm
- Paramétrable
- Boîtier cylindrique Etanche



Pare-Soleil amovible

### ● Spécifications

ITEMS	
Imaging Sensor	1/2.8" 2.1Mega Pixels SONY CMOS Sensor
Total number of pixels	1945(H) X 1109(V) = 2.16M(pixel)
Number of active pixels	1945(H) X 1097(V) = 2.13M(pixel)
Scanning Systems	Progressive Scan
Resolution	1080p(1920 X 1080)25P/30P
Min. Illumination	0.05Lux(Color) , 0.015Lux(BW)
S/N Ratio	More than 50 dB
O.S.D	Built-in
AGC	OFF / 1 ~ 15 Step
Shutter Speed	AUTO / FLICKER (NTSC : 1/30sec ~ 1/50,000sec)   (PAL : 25sec ~ 1/50,000sec)
Sense up	AUTO / OFF (x2 ~ x30)
Backlight Compensation	OFF / BLC / HSBLIC
D-WDR	ON / OFF / AUTO
Defog	AUTO / OFF
Day & Night	AUTO / B.W / COLOR / EXT (Selectable)
White Balance	ATW / AWC-SET / INDOOR / OUTDOOR / MANUAL / AWB
DNR	2DNR / 3DNR
D-EFFECT	FREEZE / MIRROR / NEG.IMAGE
Privacy Masking	ON / OFF (4 Zone Selectable)
Motion Detection	ON / OFF (4 Zone Selectable)
Defect	LIVE DPC / WHITE DPC / BLACK DPC
Adjust	SHARPNESS / MONITOR / LSC / NTSC / PAL
Language	English / German / French / Italian / Spanish / Polish / Russian / Portuguese / Dutch / Turkish / Japanese / Hebrew
Protocol	AHD (A-CP) / HD-TVI / HD-CVI / CVBS
Adjust	SHARPNESS / MONITOR / LSC / NTSC/PAL
Lens	4.0mm Fixed Mega Lens
Supplied Voltage	DC12 ±10%
Power Consumption	Max. 1.8W(150mA)

### ● Structure Specifications

MECHANICAL	
Dimension	18.8(Φ) X 74mm (without Sunshield)
Weight	0.30kg
ENVIROMENTAL	
Construction	Die-Casting (Aluminum)
Operating Temp.	-10°C ~ 50°C
Storage Temp.	0°C ~ 50°C
Humidity	0% to 90%

### OSD CONTROL



#### STEP 1.

L'accès aux menus OSD est protégé par un bouchon moleté étanche



#### STEP 2.

Dévisser le bouchon pour ouvrir la trappe



#### STEP 3.

Insérer le bouchon dans le sens inverse et le manoeuvrer en regardant l'écran pour se déplacer dans les menus

### DIMENSION

