



LTPM04

Outdoor Pan and Tilt Unit for Loads up to 15kg

IP66, maximum load of 15 kg (33.1 lb), speed adjustable pan and tilt, aluminum alloy construction



| | |
|---------------------------------------|--|
| Model | LTPM04 |
| (Movement in Horizontal Plane) | |
| Tilt Speed | 0.4° to 2.5° per second |
| Tilt Range | • -60° to 10° for load 20 kg (44.1 lb) (factory setting) |
| (Movement in Vertical Plane) | |
| Accuracy | 0.225° ± 0.003° |
| Operating Ambient Temperature | -40 °C to 70 °C (-40 °F to 158 °F) |
| Relative Humidity | 5 % to 95 % noncondensing |
| Communication | RS-485 |
| Protocols | Pelco-D, Pelco-P |
| Baud Rate | 2,400/4,800/9,600 bps adjustable |
| Standard Setting | • Available with BNC Cable (LTPM04-A-6) • Available with network cable (100Mbps) (LTPM04-N-6) |
| OSD menu | Available |
| Heater | Optional |
| Dimensions (W × H × L) | 301 mm × 217 mm × 184 mm (11.9 in × 8.5 in × 7.2 in) |
| Weight | 9.3 kg (20.5 lb) |
| Note | - |

*Design and specifications are subject to change without prior notice.

Features

- IP66, NEMA-6P enclosure rating
- Maximum load 15 kg (33.1 lb)
- Aluminum alloy construction
- Designed for indoor and outdoor applications
- Pan and tilt speed adjustable
- Support analogue or network cameras (optional)

Available Models

| Model | Support | Input Power |
|-------------------|----------|-------------|
| LTPM04-A-6 | Analogue | 24 V DC |
| LTPM04-N-6 | Network | 24 V DC |

Tech Specs

| Model | LTPM04 |
|--------------------------|--------------------------------|
| Maximum Load | 15 kg (33.1 lb) |
| Type | Indoor/Outdoor, top load |
| Protection Rating | IP66, NEMA-4X enclosure rating |
| Material | Aluminum alloy |
| Finish | Beige |
| Input Power | 24 V DC |
| Power | 40 W |
| Consumption | |
| Pan Speed | 0.4° to 10° per second |
| Pan Range | 0° to 360° continuous |